

MATERIAL SAFETY DATA SHEET

Radiator Specialty Company

1900 WILKINSON BLVD. CHARLOTTE, NC 28208 (704) 377-6555

POISON INFORMATION & EMERGENCY: 303-623-5716

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

US DEPARTMENT OF LABOR

Occupational Safety and Health Administration.
(Non-Mandatory Form) Form Approved OMB No. 1218-0072

SECTION I GENERAL INFORMATION

| | |
|---------------------|--|
| PRODUCT NAME | CARB MEDIC® CARBURETOR CLEANER (NON AEROSOL) |
| PART NUMBER | M48 – 16, 49 |

NOTE: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

| COMPONENT | WT% | C.A.S. NO. | TLV (ACGIH--X----OSHA-----) |
|--------------------------------|-------|------------|-----------------------------|
| Aliphatic Petroleum Distillate | 93-97 | 68476-34-6 | 100 ppm (Air) |

Warning: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

Comments:

Components not identified are non-hazardous according to 29 CFR 1910.1200

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

| | | | |
|--|---|------------------------------|---------------------|
| Specific Gravity (H₂O=1) | 0.84-0.88 | pH | N/A |
| Solubility in Water | Insoluble | Solubility in Solvent | Petroleum |
| Flash Point (Method) - F° | Greater than 140°F (TCC) | % Volatiles By Wt. | Greater than 90% |
| Melting Point - F° | N/A | Boiling Point - F° | Greater than 300°F. |
| Vapor Pressure (mmHg) | N/A | Vapor Density (Air=1) | N/A |
| Evaporation Rate (Butyl Acetate=1) | N/A | | |
| Appearance and Odor | Light yellow--amber liquid with petroleum odor. | | |

SECTION IV FIRE AND EXPLOSION HAZARD DATA

| | | | |
|-----------------------------|------------------------|---------------------------|-------------------------|
| EXTINGUISHING MEDIA: | Caution : COMBUSTIBLE! | | |
| Water Fog | Foam XXX | CO₂ XXX | Dry Chemical XXX |

SPECIAL FIRE FIGHTING PROCEDURES. Wear self-contained, positive pressure breathing apparatus and protective clothes.

UNUSUAL FIRE AND EXPLOSION HAZARDS None known

SECTION V REACTIVITY DATA

| | | | | | | | | |
|--------|-----|----------|-----------|----|---------------------------|-----|----|----|
| Stable | XXX | Unstable | Corrosive | NO | Hazardous Polymerization? | Yes | No | XX |
|--------|-----|----------|-----------|----|---------------------------|-----|----|----|

Incompatibilities Oxidizing agents. Open flame or sparks.

Hazardous Decomposition or Byproducts Fire: Normal products of combustion: carbon monoxide, carbon dioxide, and acrid smoke.
Nitrogen and sulfur oxides

SECTION VI HEALTH HAZARD INFORMATION

Recommended TLV of Product 100 ppm Aliphatic Petroleum Distillate

| | |
|-----------------------------|--|
| EYE CONTACT Irritant | SKIN CONTACT Irritation, Defatting, dermatitis on prolonged exposure. |
|-----------------------------|--|

| | |
|---|---|
| INHALATION Excessive inhalation may cause dizziness, headache, narcosis, irritation to mucouse membranes | INGESTION HARMFUL OR FATAL IF SWALLOWED! |
|---|---|

OTHER If aspirated into lungs, may cause lung irritation.

SECTION VII EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT Flush with water thoroughly for at least 15 min., while lifting eyelids. Consult a physician.

SKIN CONTACT Wash with soap and water thoroughly. Remove contaminated clothing and launder before re use.

INHALATION Move to fresh air. If adverse effects persist, consult a physician.

INGESTION DO NOT INDUCE VOMITING!. Drink water. DO NOT ADMINISTER EPINEPHRINE OR ADRENALINE! ! Get medical attention immediately.

SECTION VIII SPECIAL PROTECTION INFORMATION

| | CONSUMER | BULK HANDLING (Prolonged Exposure) |
|-------------------------------|-------------------------------|--|
| RESPIRATORY PROTECTION | N/A | If TLV is exceeded, wear NIOSH approved respirator |
| VENTILATION | Use with adequate ventilation | General |
| EYE PROTECTION | N/A | Goggles or full face shield |
| PROTECTIVE CLOTHING | N/A | Neoprene gloves and apron |

SECTION IX PRECAUTIONS FOR SAFE HANDLING AND USE

SPILL OR LEAK PROCEDURE Observing health hazards described above, remove ignition sources, ventilate area, wipe up with rags. Transfer to waste drum.

WASTE DISPOSAL METHOD *Dispose of in accordance with all applicable government laws and regulations.*

STORAGE AND HANDLING PRECAUTIONS Store in a cool place below 120°F. away from ignition sources and oxidizing agents.

OTHER PRECAUTIONS WEARING CONTACT LENSES IS INADVISABLE! KEEP AWAY FROM CHILDREN AND ANIMALS!

| HAZARD INFORMATION LABEL DATA | | |
|-------------------------------|--------------|------------|
| HAZARD CODE | FLAMMABILITY | REACTIVITY |
| 4- Extreme | | |
| 3- High | | |
| 2- Moderate | | |
| 1- Slight | | |
| 0- Negligible | | |

Supersedes SEPT 1998

OSHA Revised AUGUST 2000

Title R. GEER-CHEMIST

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification.