

Date : 04/15/2012

Version : 2

Material Safety Data Sheet

Quik Stik® Mini (Red/Yellow)

1. Product and company identification

Product name	: Quik Stik® Mini (Red/Yellow)
Material uses	: Marking and Identification.
Supplier/Manufacturer	: LA-CO Industries, Inc. 1201 Pratt Boulevard Elk Grove Village, IL. 60007-5746
MSDS authored by	: KMK Regulatory Services Inc.
In case of emergency	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

2. Hazards identification

This MSDS reflects the health, physical and environmental hazards of the paint released by this product. Because of the nature of the finished product i.e. the fact that the paint is in solid form, and given that the paint is released in very small amounts during normal use, the user of the product and/or the reader of this MSDS should consider the potential exposure to the paint to be minimal and controlled during the normal use of the product. Refer to relevant sections of the MSDS (7 and 13) for additional information on handling and disposal considerations.

To avoid any potential hazard and to minimize the risk of exposure, it is important that the user of the product does NOT heat, burn or expose it to a source of intense heat unless the product is specifically intended for use on hot surfaces.

Emergency overview

Physical state	: Solid in cylindrical form.
Color	: Red./Yellow.
Odor	: Not available.
Hazard statements	: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.
OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.
Routes of entry	: Not available.

Potential acute health effects

Inhalation	: Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	: No known significant effects or critical hazards.
Skin	: No known significant effects or critical hazards.
Eyes	: No known significant effects or critical hazards.

Potential chronic health effects

Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: No known significant effects or critical hazards.

Quik Stik® Mini (Red/Yellow)

2. Hazards identification

Over-exposure signs/symptoms

- Inhalation** : No specific data.
- Ingestion** : No specific data.
- Skin** : No specific data.
- Eyes** : No specific data.
- Medical conditions aggravated by over-exposure** : None known.

See toxicological information (Section 11)

3. Composition/information on ingredients

United States

Name	CAS number	%
Dipropylene glycol methyl ether	34590-94-8	30 - 60
Poly(2-propyl-m-dioxane-4,6-diylene)	63148-65-2	10 - 30
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	10 - 30
Poly(oxy-1,2-ethanediyl), alpha,alpha'-(1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl)bis(omega-hydroxy-	9014-85-1	0.1 - 1

Canada

Name	CAS number	%
Dipropylene glycol methyl ether	34590-94-8	30 - 60
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	10 - 30
Poly(oxy-1,2-ethanediyl), alpha,alpha'-(1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl)bis(omega-hydroxy-	9014-85-1	0.1 - 1

Mexico

Name	CAS number	UN number	%	IDLH	Classification			
					H	F	R	Special
Dipropylene glycol methyl ether	34590-94-8	Not regulated.	30 - 60	600 ppm	1	1	0	-
Propanoic acid, 3-ethoxy-, ethyl ester	763-69-9	UN1993	10 - 30	-	1	1	0	-
Poly(oxy-1,2-ethanediyl), alpha,alpha'-(1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl)bis(omega-hydroxy-	9014-85-1	Not regulated.	0.1 - 1	-	1	1	0	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention if symptoms occur.
- Inhalation** : Move exposed person to fresh air. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
- Protection of first-aiders** : No special protection is required.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Quik Stik® Mini (Red/Yellow)

5. Fire-fighting measures

- Flammability of the product** : No specific fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : No specific fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

- Personal precautions** : Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Avoid breathing vapor or mist. Use only with adequate ventilation. Store and use away from heat, sparks, open flame or any other ignition source.
- Storage** : Store in accordance with local regulations.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Dipropylene glycol methyl ether	<p>ACGIH TLV (United States, 2/2010). Absorbed through skin. STEL: 909 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 606 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).</p> <p>NIOSH REL (United States, 6/2009). Absorbed through skin. STEL: 900 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 600 mg/m³ 10 hour(s). TWA: 100 ppm 10 hour(s).</p> <p>OSHA PEL (United States, 6/2010). Absorbed through skin. TWA: 600 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 100 ppm 8 hour(s). TWA: 600 mg/m³ 8 hour(s). STEL: 150 ppm 15 minute(s). STEL: 900 mg/m³ 15 minute(s).</p>

Canada

Quik Stik® Mini (Red/Yellow)

8. Exposure controls/personal protection

<u>Occupational exposure limits</u>		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m ³	Other	ppm	mg/m ³	Other	ppm	mg/m ³	Other	Notations
Dipropylene glycol methyl ether	US ACGIH 2/2010	100	606	-	150	909	-	-	-	-	[1]
	AB 4/2009	100	606	-	150	909	-	-	-	-	[1]
	BC 9/2010	100	-	-	150	-	-	-	-	-	[1]
	ON 7/2010	100	606	-	150	909	-	-	-	-	[1]
	QC 6/2008	100	606	-	150	909	-	-	-	-	[1]
Propanoic acid, 3-ethoxy-, ethyl ester	ON 7/2010	50	300	-	-	-	-	-	-	-	

[1]Absorbed through skin.

Mexico

Occupational exposure limits

Ingredient	Exposure limits
Dipropylene glycol methyl ether	NOM-010-STPS (Mexico, 9/2000). Absorbed through skin. LMPE-CT: 900 mg/m ³ 15 minute(s). LMPE-CT: 150 ppm 15 minute(s). LMPE-PPT: 60 mg/m ³ 8 hour(s). LMPE-PPT: 100 ppm 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : Not required for normal use of the pen/marker. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Not required for normal use of the pen/marker. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Not required for normal use of the pen/marker. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Not required for normal use of the pen/marker. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

9. Physical and chemical properties

Physical state : Solid in cylindrical form.

Flash point : Closed cup: 61 to 93.3°C (141.8 to 199.9°F) [Pensky-Martens.]

Burning time : Not applicable.

Burning rate : Not applicable.

Auto-ignition temperature : Not available.

Flammable limits : Not available.

Color : Red./Yellow.

Odor : Not available.

Quik Stik® Mini (Red/Yellow)

9. Physical and chemical properties

Taste	: Not available.
Molecular weight	: Not applicable.
Molecular formula	: Not applicable.
pH	: Not available.
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Critical temperature	: Not available.
Relative density	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Volatility	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
SADT	: Not available.
Viscosity	: Not available.
Ionicity (in water)	: Not available.
Dispersibility properties	: Not available.
Solubility	: Not available.
Physical/chemical properties comments	: Not available.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids and alkalis.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propanoic acid, 3-ethoxy-, ethyl ester	LD50 Oral	Rat	3200 mg/kg	-

Chronic toxicity

There is no data available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dipropylene glycol methyl ether	Eyes - Mild irritant	Human	-	8 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Propanoic acid, 3-ethoxy-, ethyl ester	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-

Sensitizer

Skin : There is no data available.

Respiratory : There is no data available.

Carcinogenicity

Quik Stik® Mini (Red/Yellow)

11. Toxicological information

There is no data available.

Mutagenicity

There is no data available.

Teratogenicity

There is no data available.

Reproductive toxicity

There is no data available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Propanoic acid, 3-ethoxy-, ethyl ester	EC50 >480 mg/l	Daphnia	48 hours

Persistence/degradability

There is no data available.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

DOT/TDG/MXT/IMDG/IATA : Not regulated.

15. Regulatory information

United States

HCS Classification : Not regulated.

U.S. Federal regulations : TSCA 8(a) PAIR: Dipropylene glycol methyl ether

TSCA 8(a) IUR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Dipropylene glycol methyl ether

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:

Dipropylene glycol methyl ether: Fire hazard, Immediate (acute) health hazard

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

Quik Stik® Mini (Red/Yellow)

15. Regulatory information

DEA List II Chemicals (Essential Chemicals) : Not listed

State regulations

Massachusetts : The following components are listed: Dipropylene glycol methyl ether
New York : None of the components are listed.
New Jersey : The following components are listed: Dipropylene glycol methyl ether
Pennsylvania : The following components are listed: Dipropylene glycol methyl ether
California Prop. 65
 No products were found.

Canada

WHMIS (Canada) : Not controlled under WHMIS (Canada).


Canadian lists

Canadian NPRI : None of the components are listed.
CEPA Toxic substances : None of the components are listed.
Canada inventory : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Mexico

Classification :



16. Other information

Label requirements : NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.

Hazardous Material Information System (U.S.A.) : **Health** : 0 **Flammability** : 1 **Physical hazards** : 0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) : **Health** : 0 **Flammability** : 1 **Instability** : 0

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue mm/dd/yyyy : 04/15/2012
Date of previous issue : 11/15/2011

Quik Stik® Mini (Red/Yellow)

16. Other information

Version : 2

Revised Section(s) : 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.