

Permatex, Inc.  
 10 Columbus Blvd.  
 Hartford, CT 06106 USA  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Emergency: 800-255-3924 (ChemTel)  
 International Emergency: +01-813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** FUEL TANK & RADIATOR REPAIR KIT PRS  
**Item No:** 09116  
**Product Type:** Epoxy

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
LIMESTONE 1317-65-3	40-60	Not listed	15 mg/m <sup>3</sup>
MAGNESIUM SILICATE 14807-96-6	20-40	2 mg/m <sup>3</sup>	20 mppcf
MERCAPTAN AMINE BLEND MIXTURE	10-20	Not listed	Not listed
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	10-20	Not listed	Not listed
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye, skin and respiratory irritation. May cause skin sensitization. May cause gastrointestinal irritation.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness. Eye irritation may be severe and result in injury. Repeated skin contact may cause allergic skin reactions. Moderately toxic if swallowed. Irritating to mouth, throat and stomach with nausea. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
MAGNESIUM SILICATE 14807-96-6	20-40	male rat-some evidence, female rat-clear evidence, male mice-no evidence, female mice-no evidence	A4-Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
TITANIUM DIOXIDE 13463-67-7	0.1-1.0	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989

**Medical Conditions Recognized as Being Aggravated by Exposure:** Preexisting skin disorders. Persons with respiratory problems such as emphysema and asthma should avoid inhalation.

### 4. FIRST AID MEASURES

**Ingestion:** Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Rinse immediately with plenty of water for at least 15 minutes. Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## 5. FIRE FIGHTING MEASURES

<b>Flash Point °F(C°):</b>	>300° F TCC
<b>Recommended Extinguishing Media:</b>	Carbon Dioxide, Dry Chemicals, Foam.
<b>Special Fire-Fighting Procedures:</b>	Firefighters should wear self-contained breathing apparatus.
<b>Hazardous Products of Combustion:</b>	Oxides of carbon, Nitrogen, Oxides of sulfur, Aldehydes, Acid vapors, Ammonia
<b>Unusual Fire/Explosion Hazards:</b>	Heating above 149°C (300°F) in the presence of air may cause slow oxidation decomposition and above 260°C (500°F) may cause polymerization.
<b>Lower Explosive Limit:</b>	Not determined.
<b>Upper Explosive Limit:</b>	Not determined.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spill Procedures:</b>	Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers.
--------------------------	--

## 7. HANDLING AND STORAGE

<b>Storage:</b>	Store in a cool, dry area. Store below 100°F.
<b>Handling:</b>	Avoid contact with skin and eyes. Do not inhale vapors. Use in a well ventilated area to prevent irritation by vapors. Wash thoroughly after handling. Discard contaminated leather gloves and shoes.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Eyes:</b>	Safety glasses.
<b>Skin:</b>	Neoprene or nitrile gloves recommended.
<b>Ventilation:</b>	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
<b>Respiratory Protection:</b>	An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Black putty
<b>Odor:</b>	Mercaptan
<b>Boiling Point:</b>	>400°F
<b>pH:</b>	Does not apply
<b>Solubility in Water:</b>	Nil
<b>Specific Gravity:</b>	1.9
<b>VOC(Wt.%):</b>	0
<b>Vapor Pressure:</b>	Nil
<b>Vapor Density (Air=1):</b>	>1
<b>Evaporation Rate:</b>	<1 (butyl acetate = 1)

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability:</b>	Stable at normal conditions
<b>Hazardous Polymerization:</b>	Will not occur
<b>Incompatibilities:</b>	Strong Lewis or mineral acids, strong oxidizing agents, strong mineral and organic bases (especially primary and secondary aliphatic amines)
<b>Conditions to Avoid:</b>	Heat.
<b>Hazardous Products of Combustion:</b>	Oxides of carbon, Nitrogen, Oxides of sulfur, Aldehydes, Acid vapors, Ammonia

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

<b>Recommended Method of Disposal:</b>	Dispose of in accordance with local, state and federal regulations.
<b>US EPA Waste Number:</b>	NH - Not a RCRA Hazardous Waste Material

**Product Name:** FUEL TANK & RADIATOR REPAIR KIT  
PRS

**Item No:** 09116

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### Ground Transport (DOT)

**DOT Shipping Name:** Not regulated  
**Hazard Class:** None  
**UN/ID Number:** None

### IATA

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/ID Number:** None

### IMDG

**Proper Shipping:** Not regulated  
**Hazard Class:** None  
**UN Number:** None  
  
**Marine Pollutant:** None

## 15. REGULATORY INFORMATION

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** June 28, 2011

**Revision Number:** 5

**Telephone No.:** 1-87-Permatex (877) 376-2839