

MSDS Material Safety Data Sheet

THE PENRAY COMPANIES, INC.



PENRAY NON-CHLORINATED ULTRA LOW VOC BRAKE CLEANER - 4705

MSDS Number: 4705

Revision Date: 03/31/2009

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

The Penray Companies, Inc.

440 Denniston Ct.
Wheeling, IL 60090

Contact: EH&S Manager
Telephone Number: 847-459-5000
FAX Number: 847-459-5043
E-Mail:
Web www.penray.com

Product Name: PENRAY NON-CHLORINATED ULTRA LOW VOC BRAKE CLEANER - 4705
Revision Date: 03/31/2009
MSDS Number: 4705
Common Name: BRAKE CLEANER CONTAINING ORGANIC SOLVENTS
Chemical Formula: F4705

EMERGENCY PHONE NUMBER (800) 752-7869

NFPA 704M RATING :

HEALTH:2 FIRE:4 REACTIVITY:0 SPECIAL:

0=INSIGNIFICANT 1=SLIGHT 2=MODERATE 3=HIGH 4=EXTREME

2 COMPOSITION/INFORMATION ON INGREDIENTS

ACETONE	67-64-1	80-100%
TOLUENE	108-88-3	0-10%

3 HAZARDS IDENTIFICATION

Route of Entry: Skin absorption and inhalation
Target Organs: Lungs, kidneys, liver and nervous system.
Inhalation: Respiratory irritation and dizziness
Skin Contact: Prolonged contact with skin can cause irritation. Repeated skin contact may cause persistent irritation and dermatitis
Eye Contact: Will cause irritation upon contact.
Ingestion: Product may cause discomfort, nausea, vomiting and diarrhea.

CARCINOGENICITY: Product is not considered a carcinogen by OSHA, NTP or IARC.
MEDICAL CONDITIONS: Pre-existing eye or skin conditions may be aggravated by over-exposure to this product.

MSDS Material Safety Data Sheet

THE PENRAY COMPANIES, INC.



PENRAY NON-CHLORINATED ULTRA LOW VOC BRAKE CLEANER - 4705

MSDS Number: 4705

Revision Date 03/31/2009

Page 2 of 4

4 FIRST AID MEASURES

- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. Seek medical attention. Inhalation hazard unlikely due to low volatility of product.
- Skin Contact:** Wash area with soap and water. seek medical attention if irritation persists
- Eye Contact:** Immediately flush eyes with plenty of water for 15 minutes. Seek medical attention.
- Ingestion:** DO NOT induce vomiting. Only give CONSCIOUS victim two glasses of water and seek medical attention. NEVER give UNCONSCIOUS anything by mouth.

5 FIRE FIGHTING MEASURES

- Flash Point:** 0 degrees F
- Flash Point Method:** TCC
- LEL:** 2.5
- UEL:** 12.8

EXTINGUISHING MEDIA: Carbon Dioxide (CO2) Dry Chemical, Foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can collect in low areas

FIRE FIGHTING INSTRUCTIONS: Containers can build up pressure if exposed to fire. Containers should be cooled with water supply.

FIRE FIGHTING EQUIPMENT: Self- contained breathing apparatus with full face piece operated in positive pressure mode.

6 ACCIDENTAL RELEASE MEASURES

SPILL/LEAK PROCEDURES: Notify safety personnel ,evacuate all unnecessary personnel and provide adequate ventilation. If feasible, and without risk, clean-up personnel should stop leak. All clean up personnel should wear proper personal protective equipment.

SMALL SPILLS: Clean with inert absorbent and place in recovery drums for disposal.

LARGE SPILLS: Dike to prevent further migration of material. DO NOT release into waterways or sewers. Follow applicable federal and state regulations.

7 HANDLING AND STORAGE

- Handling Precautions:** Wash thoroughly after handling. Do not get into eyes, on skin or on clothing.. Do not smoke while using this product. Do not use near excessive heat, sparks, or open flame.
- Storage Requirements:** Store in clean, dry locations away from excessive heat. Store in areas designated for the storage of Level III aerosols according to NFPA 30B (Manufacturing and Storage of Aerosol Products.)

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering Controls:** Eye wash station and safety shower.
Strong general ventilation or local exhaust.
- Protective Equipment:** EYE: Chemical splash goggles with indirect or no ventilation.
SKIN :Chemical resistant gloves, such as nitrile.
RESPIRATORY: Organic vapor air purifying respirator if vapors are a nuisance or if the concentrations are above PEL or TLV.

Exposure Guidelines/Other: Never eat, drink or smoke in work area

MSDS Material Safety Data Sheet

THE PENRAY COMPANIES, INC.



PENRAY NON-CHLORINATED ULTRA LOW VOC BRAKE CLEANER - 4705

MSDS Number: 4705

Revision Date: 03/31/2009

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless liquid	Boiling Point:	133 - 189 F
Physical State:	liquid	Freezing/Melting Pt.:	
Odor:	Sweet pungent	Solubility:	soluble in water
pH:		Spec Grav./Density:	0.7955
Vapor Pressure:			
Vapor Density:			
VOC:	3 %		
Evap. Rate:	>1.0		

10 STABILITY AND REACTIVITY

Stability:	Material is stable.
Conditions to avoid:	Excessive heat and open flame.
Materials to avoid (incompatibility):	Strong oxidizing agents.
Hazardous Decomposition products:	Carbon Monoxide and Carbon Dioxide
Hazardous Polymerization:	Cannot occur.

11 TOXICOLOGICAL INFORMATION

LD50

Acetone:	10.7 ml/kg (oral)
Toluene	7.53 gm/kg (oral)

12 ECOLOGICAL INFORMATION

No data.

13 DISPOSAL CONSIDERATIONS

As a waste, this product in its raw form DOES MEET the criteria of a hazardous waste as defined by RCRA (40 CFR 361). All used and unused product and container should be disposed of in accordance with all applicable federal, state and local regulations. Do not dump in drains, sewers, on the ground or into any body of water.

14 TRANSPORT INFORMATION

DOMESTIC: Flammable Liquids, n.o.s., (Acetone), Class 3, UN1993, PGII.

EXPORT: Flammable Liquids, n.o.s., (Acetone), Class 3, UN1993, PGII, FP -16 Ccc.

MSDS Material Safety Data Sheet

THE PENRAY COMPANIES, INC.



PENRAY NON-CHLORINATED ULTRA LOW VOC BRAKE CLEANER - 4705

MSDS Number: 4705

Revision Date: 03/31/2009

Page 4 of 4

15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA: Considered to be a hazardous material as defined by 29CFR1910.1200

EPA SARA TITLE III

Section 311-312 (40CFR370): If stored in excess of the threshold quantities, this product should be reported as a(n):

IMMEDIATE (acute) HEALTH HAZARD

DELAYED (chronic) HEALTH HAZARD

FIRE HAZARD

SUDDEN RELEASE HAZARD

Section 313(40CFR372) This product does contain ingredients which are subject to the reporting requirements of SARA 313.

Toluene 108-88-3 3.000%

16 OTHER INFORMATION

CALIFORNIA PROPOSITION 65: This product does contain chemicals known to the State of California to cause birth defects and other reproductive harm.

Toluene

Meets the California South Coast Air Quality Management District VOC regulatory compliant rules 1171 & 102 contains 0.1990341 lbs of VOC per gallon. Regulatory limit is 0.21 lbs of VOC per gallon.

END OF MSDS DOCUMENT