

MSDS FOR: LN-601

Adhesive
for # 45019

REVISED: 07-JAN-2004

SECTION 1:

PRODUCT IDENTIFIER: LN-601 FOR PROJECTS & CONSTRUCTION

DATE OF PREPARATION: JANUARY 7, 2004

PRODUCT USE: ADHESIVE

MANUFACTURED BY: MACCO ADHESIVES
925 EUCLID AVENUE
CLEVELAND, OHIO 44115, U.S.A.ICI PAINTS CANADA
8200 KEELE STREET
CONCORD, ONTARIO L4K 2A5, CANADA

EMERGENCY AND MSDS TELEPHONE NUMBER: 1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	WT%
CHEMICAL NAME: 2-METHYLPENTANE COMMON NAME: 2-METHYLPENTANE CAS NUMBER: 107-83-5	5-10
CHEMICAL NAME: LIMESTONE COMMON NAME: LIMESTONE CAS NUMBER: 1317-65-3	20-30
CHEMICAL NAME: KAOLIN COMMON NAME: CLAY CAS NUMBER: 1332-58-7	20-30
CHEMICAL NAME: QUARTZ COMMON NAME: QUARTZ CAS NUMBER: 14808-60-7	.1-1.0
CHEMICAL NAME: BENZENE, 1,3-DIETHENYL-, POLYMER WITH 1,3-BUTADIENE AND ETHENYLBENZENE COMMON NAME: STYRENE-BUTADIENE POLYMER CAS NUMBER: 26471-45-4	1-5
CHEMICAL NAME: SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC COMMON NAME: LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM) CAS NUMBER: 64742-89-8	10-20
CHEMICAL NAME: DISTILLATES (PETROLEUM), STEAM-CRACKED, POLYMERS WITH LIGHT STEAM-CRACKED PETROLEUM NAPHTHA COMMON NAME: AROMATIC HYDROCARBON RESIN CAS NUMBER: 68410-16-2	10-20

CHEMICAL NAME:	2,2-DIMETHYLBUTANE	1-5
COMMON NAME:	DIMETHYLBUTANE	
CAS NUMBER:	75-83-2	
CHEMICAL NAME:	2,3-DIMETHYLBUTANE	1-5
COMMON NAME:	DIMETHYLBUTANE	
CAS NUMBER:	79-29-8	
CHEMICAL NAME:	BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE	1-5
COMMON NAME:	STYRENE-BUTADIENE POLYMER	
CAS NUMBER:	9003-55-8	
CHEMICAL NAME:	3-METHYLPENTANE	1-5
COMMON NAME:	3-METHYL PENTANE	
CAS NUMBER:	96-14-0	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE: INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION

EFFECTS OF OVEREXPOSURE

INHALATION: IRRITATION OF RESPIRATORY TRACT. PROLONGED INHALATION MAY LEAD TO LOSS OF APPETITE, MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, COUGHING, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, CONVULSIONS, PNEUMOCONIOSIS, LOSS OF CONSCIOUSNESS, DEATH.

SKIN CONTACT: IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING.

EYE CONTACT: IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES, SEVERE EYE IRRITATION.

INGESTION: INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, DIFFICULTY OF BREATHING, CONVULSIONS, PARALYSIS, CARDIAC FAILURE, DEATH.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

EYE, SKIN, RESPIRATORY DISORDERS, LUNG DISORDERS

LARGE SPILLS: SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS: USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7: HANDLING AND STORAGE

STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS:

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME: 2-METHYLPENTANE
CAS NUMBER: 107-83-5
ACGIH(TWA): 500 PPM
ACGIH(STEL): C 1000 PPM

COMMON NAME: LIMESTONE
CAS NUMBER: 1317-65-3
ACGIH(TWA): 10 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: CLAY
CAS NUMBER: 1332-58-7
ACGIH(TWA): 2 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME: QUARTZ
CAS NUMBER: 14808-60-7
ACGIH(TWA): .05 MG/M3 OSHA(TWA): 0.1 MG/M3

COMMON NAME: LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)
CAS NUMBER: 64742-89-8
OSHA(TWA): 300 PPM

COMMON NAME: DIMETHYLBUTANE
CAS NUMBER: 75-83-2
ACGIH(TWA): 500 PPM
ACGIH(STEL): 1000 PPM

COMMON NAME: DIMETHYLBUTANE
CAS NUMBER: 79-29-8
ACGIH(TWA): 500 PPM
ACGIH(STEL): 1000 PPM

COMMON NAME: 3-METHYL PENTANE
 CAS NUMBER: 96-14-0
 ACGIH(TWA): 500 PPM
 ACGIH(STEL): 1000 PPM

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING- SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION: PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS. USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT: EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES. IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.132
BOILING RANGE (F/C):	122-185/ 50- 85	WEIGHT PER GALLON:	9.43/ 11.32IMP
%VOLATILE BY VOLUME:	57.74	PHYSICAL STATE:	PASTE
APPEARANCE:	TAN	SOLUBLE IN WATER:	N
PH:	NOT APPLICABLE		

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS: STABLE - SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID: OXIDIZERS, ACIDS, STYRENE MONOMER.

CONDITIONS TO AVOID: ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, SPARKS, OPEN FLAME, IGNITION SOURCES

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME:	2-METHYL PENTANE			
CAS NUMBER:	107-83-5			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO

COMMON NAME:	LIMESTONE			
CAS NUMBER:	1317-65-3			
CARCINOGENICITY LISTED BY:	NTP NO	IARC NO	OSHA NO	ACGIH NO
LD50:	6450.00 MG/KG ORI. RAT			

COMMON NAME: CLAY
CAS NUMBER: 1332-58-7
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: QUARTZ
CAS NUMBER: 14808-60-7
CARCINOGENICITY LISTED BY: NTP YES IARC YES 1 OSHA NO ACGIH NO

COMMON NAME: LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)
CAS NUMBER: 64742-89-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50:> 3.16 GM/KG SKN RBT
LD50:> 5.00 GM/KG ORL RAT

COMMON NAME: AROMATIC HYDROCARBON RESIN
CAS NUMBER: 68410-16-2
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: DIMETHYLBUTANE
CAS NUMBER: 75-83-2
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: DIMETHYLBUTANE
CAS NUMBER: 79-29-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: STYRENE-BUTADIENE POLYMER
CAS NUMBER: 9003-55-8
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME: 3-METHYL PENTANE
CAS NUMBER: 96-14-0
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.

NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO CENTRAL NERVOUS SYSTEM.

CARCINOGENICITY: CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. THE NATIONAL TOXICOLOGY PROGRAM (NTP) HAS CLASSIFIED CRYSTALLINE SILICA AS A KNOWN HUMAN CARCINOGEN.

REPRODUCTIVE EFFECTS: NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY: NO MUTAGENIC EFFECTS ARE ANTICIPATED
TERATOGENICITY: NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.
AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT: ADHESIVES, 3, UN1133, PGIII
IMDG: ADHESIVES, CLASS 3, UN1133, PGIII, LIMITED QUANTITY,
ADHESIVES, CLASS 3, UN1133, PGIII
IATA: CONSUMER COMMODITY, 9, ID8000
TDG: NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

SARA	SARA	CERCLA	HAZ AIR	MARINE
302	313	302.4	POLLUTANT	POLLUTANT

THIS PRODUCT CONTAINS NO SARA 302, CERCLA 302.4 OR HAZARDOUS AIR POLLUTANT CHEMICALS. IT ALSO CONTAINS NO CHEMICALS WHICH ARE SUBJECT TO THE REPORTING REQUIREMENTS UNDER SARA 313. AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) & THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL. COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.