

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Material number : 000000000001047443

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Emergency** : In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Vehicle Maintenance

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

| | |
|------------|-------------------------------------|
| Appearance | Aerosol containing a compressed gas |
| Colour | red |
| Odour | solvent-like |

GHS Classification

Flammable aerosols : Category 1
 Gases under pressure : Compressed gas
 Acute toxicity (Inhalation) : Category 4
 Skin irritation : Category 2
 Eye irritation : Category 2A
 Carcinogenicity : Category 2
 Specific target organ toxicity - single exposure : Category 3 (Central nervous system)





GHS label elements

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

| | | |
|--------------------------|---|---|
| Hazard pictograms | : |     |
| Signal word | : | Danger |
| Hazard statements | : | H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. |
| Precautionary statements | : | Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: P501 Dispose of contents/container in accordance with local regulation. |

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---|-------------|-------------------|
| acetone | 67-64-1 | >= 30 - < 50 |
| Fuel oil, no. 2 | 68476-30-2 | >= 30 - < 50 |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | >= 10 - < 20 |
| carbon dioxide | 124-38-9 | >= 5 - < 10 |
| 4-Nonylphenol branched, ethoxylated | 127087-87-0 | >= 1 - < 3 |
| Solvent naphtha (petroleum), heavy aliph. | 64742-96-7 | >= 1 - < 3 |
| naphthalene | 91-20-3 | >= 0.1 - < 1 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
- In case of skin contact : Wash off with soap and water.
If skin irritation persists, call a physician.
If on clothes, remove clothes.
Wash off immediately with plenty of water for at least 15 minutes.
Wash contaminated clothing before re-use.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness.
Chronic effects are delayed and symptoms may not be observed during an exposure.
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

Effects are dependent on exposure (dose, concentration, contact time).

Causes skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

May cause drowsiness or dizziness.

May cause cancer.

Review section 2 of SDS to see all potential hazards.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke

Specific extinguishing methods :

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Do not breathe vapours or spray mist. Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents
Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|---------|-------------------------------|--|-----------|
| acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m ³ | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m ³ | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m ³ | OSHA P0 |
| | | STEL | 1,000 ppm | OSHA P0 |

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

| | | | | |
|--|------------|----------------------|----------------------------|-----------|
| | | | 2,400 mg/m3 | |
| | | STEL | 750 ppm 1,780 mg/m3 | CAL PEL |
| | | C | 3,000 ppm | CAL PEL |
| | | PEL | 500 ppm 1,200 mg/m3 | CAL PEL |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | TWA | 500 ppm 2,000 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| | | TWA (Mist) | 5 mg/m3 | OSHA P0 |
| | | TWA (Mist) | 5 mg/m3 | NIOSH REL |
| | | ST (Mist) | 10 mg/m3 | NIOSH REL |
| | | PEL (particulate) | 5 mg/m3 | CAL PEL |
| carbon dioxide | 124-38-9 | TWA | 5,000 ppm | ACGIH |
| | | STEL | 30,000 ppm | ACGIH |
| | | TWA | 5,000 ppm 9,000 mg/m3 | NIOSH REL |
| | | ST | 30,000 ppm 54,000 mg/m3 | NIOSH REL |
| | | TWA | 5,000 ppm 9,000 mg/m3 | OSHA Z-1 |
| | | TWA | 10,000 ppm 18,000 mg/m3 | OSHA P0 |
| | | STEL | 30,000 ppm 54,000 mg/m3 | OSHA P0 |
| | | PEL | 5,000 ppm 9,000 mg/m3 | CAL PEL |
| | | STEL | 30,000 ppm 54,000 mg/m3 | CAL PEL |
| naphthalene | 91-20-3 | TWA | 10 ppm | ACGIH |
| | | STEL | 15 ppm | ACGIH |
| | | TWA | 10 ppm 50 mg/m3 | NIOSH REL |
| | | ST | 15 ppm 75 mg/m3 | NIOSH REL |
| | | TWA | 10 ppm 50 mg/m3 | OSHA Z-1 |
| | | TWA | 10 ppm 50 mg/m3 | OSHA P0 |
| | | STEL | 15 ppm 75 mg/m3 | OSHA P0 |
| | | PEL | 0.1 ppm 0.5 mg/m3 | CAL PEL |

Biological occupational exposure limits

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|---|---------------------------|-----------|
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after | 25 mg/l | ACGIH BEI |

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

| | | | | | | |
|--|--|--|--|------------------|--|--|
| | | | | exposure ceases) | | |
|--|--|--|--|------------------|--|--|

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

: Protective gloves

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : red

Odour : solvent-like

pH : No data available

Melting point/freezing point : No data available

Boiling point : No data available

Flash point

:
Not applicable

Evaporation rate

: No data available

Flammability (solid, gas)

: Extremely flammable aerosol.

Upper explosion limit

: No data available

Lower explosion limit

: No data available

Density

: 0.83 g/cm³

Solubility(ies)

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

| | |
|--|---------------------|
| Water solubility | : partly soluble |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : 45.19 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. |
| Conditions to avoid | : Heat, flames and sparks. |
| Incompatible materials | : Acids Strong oxidizing agents |
| Hazardous decomposition products | : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Smoke |

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

| | |
|------------------------------|---|
| Aggravated Medical Condition | : None known. |
| Symptoms of Overexposure | : Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. Chronic effects are delayed and symptoms may not be observed during an exposure. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions. Effects are dependent on exposure (dose, concentration, contact time). |

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

Carcinogenicity:

| | | |
|--------------|--|---------|
| IARC | Group 2B: Possibly carcinogenic to humans naphthalene | 91-20-3 |
| ACGIH | Confirmed animal carcinogen with unknown relevance to humans naphthalene | 91-20-3 |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. | |
| NTP | Reasonably anticipated to be a human carcinogen naphthalene | 91-20-3 |

Acute toxicity**Product:**

Acute inhalation toxicity : Acute toxicity estimate : 4.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**acetone:**

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

Distillates (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg

Acute inhalation toxicity : LC50 Rat: > 4.6 mg/l
Exposure time: 6 h

Acute dermal toxicity : LD50 Rat: > 2,000 mg/kg

4-Nonylphenol branched, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: 16,000 mg/kg

Acute dermal toxicity : LD50 Rabbit: 2,573 mg/kg

Skin corrosion/irritation

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

Product:

Remarks: Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated light:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

Partition coefficient: n-octanol/water : Remarks: No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

Components:**Distillates (petroleum), hydrotreated light :**

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

| |
|--|
| Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|--|

| |
|---|
| Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity |
|---|

| |
|--|
| Transportation Regulation: IATA (Cargo Air): |
|--|

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

 Transportation Regulation: IATA (Passenger Air):
 UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

 Transportation Regulation: TDG (Canada):
 UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
 naphthalene 91-20-3

EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|---------|--------------------|-----------------------------|
| acetone | 67-64-1 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Gases under pressure
 Acute toxicity (any route of exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Carcinogenicity
 Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:
 naphthalene 91-20-3 0.1662 %

California Prop. 65

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023



WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.


Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

| | |
|------------------------|-----------|
| HEALTH | 2* |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 3 |

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms :



Signal word :

Danger:

Hazard statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary statements :

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/

A00376 ZP AUTO ENG DEG ZAA376_12CS 20N15

Version 2.0

Revision Date 04/30/2018

Print Date 06/16/2023

protective clothing/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

| | |
|----------------|------------|
| Version: | 2.0 |
| Revision Date: | 04/30/2018 |
| Print Date: | 06/16/2023 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.